



Installation Instructions

Description: SADDLEMEN SISSY BAR PADS

Application: HARLEY DAVIDSON (EXCEPT DUECE) & UNIVERSAL

Contents:	Ref.	Description	Qty.	Tools Required
	1.	Saddlemen Sissybar Pad	1	Phillip's Screwdriver
	2.	Instruction Sheet	1	Awl or Ice pick
	3.	Template	1	
	4.	1/4" x 20 x 3/4" Pan Head Screws	4	
	5.	Universal Mounting Bracket	2	

IMPORTANT: preparation prior to installation

Please read and follow these instructions carefully. To emphasize information, the symbols and the words **WARNING** and **CAUTION** have special meanings. Pay close attention to the messages highlighted by these signal words.

NOTE: Indicates special information to make maintenance easier or the instructions clearer: Read and understand the instructions completely before starting to avoid possible injury to yourself or damage to the motorcycle and/or accessory.

NOTICE TO DEALER: These instructions contain important information for future reference and should be given to the customer.

Installation:

1. If replacing an existing sissy bar pad, remove the old pad, brackets and screws.
2. Select the template which matches the profile of your new Saddlemen Sissybar pad and choose the installation below which corresponds to your motorcycle.

Universal Mounting or Harley Davidson Sissybars without center plate

- 3a. Note the hole pattern marked (A) on the template. These 4 holes will be used to secure the two mounting brackets supplied. These 2 brackets will clamp around the sissy bar upright bars to mount the pad. Before proceeding, measure the width of the inside dimension of the sissybar. This mounting is designed for a 4" to 4 5/8" inside dimension only.
- 4a. Transfer the position of the four holes marked (A) to the back, of the sissybar pad (opposite side of the decorated face).
- 5a. This is done by aligning the template over the pad and feeling for depressions in the back of the pad which match up with the corresponding (A) circles on the template. Fine adjustment of the four circles marked (A) on the template directly over the depressions below the pad cover may be necessary. Use a sharp pointed tool (such as an awl or an icepick) and using the template as a guide, puncture the circles marked (A) for the four screws in the back of the pad. This will expose the threads for the screws.
- 6a. Position the backrest on the sissy bar as desired. Insert one 1/4" x 20 pan head screw into the mounting bracket provided and sandwich the sissybar between the pad and the mounting bracket by aligning the holes in the pad back with the bracket and lightly tightening the pan head screw into the mounting plate of the sissybar pad. Insert one 1/4" x 20 pan head screw in the remaining hole and tighten both screws securely.
- 7a. Repeat the process for the other mounting holes.

Harley Davidson Road King

- 1b. Note the hole pattern marked (B) on the template. This 3 hole pattern is designed to mount to a stock Harley Davidson Road King using the three mounting holes provided on the center plate attached to the sissybar.
- 2b. Transfer the position of the four holes marked (B) to the back, of the sissybar pad (opposite side of the decorated face).
- 3b. This is done by aligning the template over the pad and feeling for depressions in the back of the pad which match up with the corresponding (B) circles on the template. Fine adjustment of the three circles marked (B) on the template directly over the depressions below the pad cover may be necessary. Use a sharp pointed tool (such as an awl or an icepick) and using the template as a guide, puncture the circles marked (B) for the three screws in the back of the pad. This will expose the threads for the screws.



Installation Instructions (page 2)

Description: SADDLEMEN SISSY BAR PADS

Application: HARLEY DAVIDSON (EXCEPT DUECE) & UNIVERSAL

Installation:

- 4b. Position the backrest by aligning the newly punctured holes with the holes in the sissy bar mounting plate. Insert three of the supplied 1/4" x 20 pan head screws into the sissy bar pad through the holes in the mounting plate and tighten securely.

Harley Davidson Sissybars with centerplate

- 1c. Note the hole pattern marked (C) on the template. This 3 hole pattern is designed is to fit most stock Harley Davidson Sissybars that are equipped with a center plate with a single center hole. This center hole and one at the two universal mounting brackets will be utilized to mount the pad. Before proceeding, measure the width of the inside dimension of the sissybar. This mounting is designed for a 4" to 4 5/8" inside dimension only.
- 2c. Transfer the position of the four holes marked (c) to the back, of the sissybar pad (opposite side of the decorated face).
- 3c. This is done by aligning the template over the pad and feeling for depressions in the back of the pad which match up with the corresponding (c) circles on the template. Fine adjustment of the three circles marked (c) on the template directly over the depressions below the pad cover may be necessary. Use a sharp pointed tool (such as an awl or an icepick) and using the template as a guide, puncture the circles marked (c) for the three screws in the back of the pad. This will expose the threads for the screws.
- 4c. Position and mount the Saddlemen Sissybar Pad to the sissybar by aligning the top hole in the back of the pad with hole in the centerplate. Insert one 1/4" x 20 pan screw and hand tighten. Insert one 1/4" x 20 pan head screw into one supplied mounting bracket provided and sandwich the sissybar between the pad and the mounting bracket by aligning the holes in the pad back with the bracket and hand tightening the pan head screw into the mounting plate of the sissybar pad. Insert one 1/4" x 20 pan head screw in the remaining hole and tighten all three screw securely.

Installation Notes:

Universal Mounting installation requires:

- 1 - Saddlemen Sissybar Pad
- 4 - 1/4" x 20 x 3/4"
- 2 - Universal Mounting Bracket

Harley Davidson Road King installation requires:

- 1 - Saddlemen Sissybar Pad
- 3 - 1/4" x 20 x 3/4"

Harley Davidson Sissybars with centerplate:

- 1 - Saddlemen Sissybar Pad
- 3 - 1/4" x 20 x 3/4"
- 1 - Universal Mounting Bracket

*Check to be sure that there is no interference with any moving parts or wiring.

**Re-check the bolts after 100 miles. Enjoy the ride..

NOTE:



Maintenance: Materials used on our products can be cleaned with a damp cloth and maintained with quality commercial vinyl and leather preservatives. Saddlemen's Seat and Saddlebag **Ultra Wash** and **Conditioner's** combats grease, oil, dirt and stains. Saddlemen Cleaning Products are developed specifically to keep leather, Saddlehyde, fabric and vinyl looking like new. Use on Seats, saddlebags, sissybar bags, jackets and other motorcycle apparel. **WARNING-AVOID TREATMENTS THAT CREATE SLIPPERY SEATING SURFACES**

